CARABINER AND CINCH LOOP TOOL LANYARD-4.5 KG

Fall Protection System

FOXSAFE TL22

FOX UK

SCOPE:

Foxsafe tool lanyard TL22 attaches to the user's wrist with Velcro. Tools are attached by cinching the lanyard cord around the tool. The TL22 features an adjustable Velcro wrist strap for attachment to the worker. The bandit tool holder features attachment to the elasticized webbing wrist and the tool via a mini carabiner.

KEY FEATURES:

- **Compliance with ANSI standard to ensure maximum safety** The ANSI/ISEA 121-2018 standard includes design, testing, performance and labelling requirements for tool tethering systems.
- **Light weight webbing/Elasticized tool straps** which contain tools whilst working at height. These units feature a cord to connect to a tool, and a wrist strap for connection to the worker.
- **Durable** Made with shock-absorbing tubular nylon webbing and lock stitching at both ends for added security.
- **Locking Aluminum Carabiner** For easy secure attachment to the tools.
- Good Corrosion resistance and strength.
- Ergonomically designed to ensure convenient portability and can be used to tether multiple tools.
- Well-contoured structure lends a comfortable grip.
- Dynamic load tested.

DISPLAY:



DATA SHEET	
PRODUCT:	Carabiner and Cinch Loop Tool Lanyard
BRAND:	FOXSAFE
MODEL:	TL22
CARABINERS:	Locking, Single Carabiner
LANYARD TYPE:	Shock Absorbing
MATERIALS:	Aluminum, Elastic, Nylon
MAX RESTING WEIGHT RATINGH:	14 lbs / 6 Kg
SAFE WORKING LOADD:	10 lbs / 4.5 kg
PRODUCT TYPE	Lanyard
RISK INJURY:	Falling Objects
STANDARDS/COMPLIANCE:	ANSI / ISEA 121-2018
COUNTRY OF MANUFACTURING:	Korea

WARNING

ALL TOOLS MUST BE TETHERED WHEN WORKING AT HEIGHT

STANDARD

ANSI / ISEA 121-2018

FOXUK FOXUK FOXUK FOXUK FOXUK FOXUK FOXUK FOXUK